

客 户

CUSTOMER_____

承 认 书

SPECIFICATION FOR APPROVAL

客 户 编 号

CUSTOMER PART NO: _____

品 名 编 号

DESCRIPTION NO. _____TAG-915M08

提 出 日 期

PRESENT DAY : _____2014-12-01

出 图 DRAWING			客户承认 CUSTOMER APPROVE
发 行 MADE	检 查 CHECKED	承 认 APPROVED	
Dence	Boby	Henry	
DATE: 2014.11.01			DATE:

深圳市铨顺宏科技有限公司


ShenZhen Fuwit Technology Co., Ltd.

表单编号: ST-R03-10

PRODUCT SPECIFICATION

TAG-915M08 为无源超高频遠距離抗金属标签，广泛适用于户外金属设备管理、混泥土管理（埋入水泥里 3CM，具有优质的读取性能）。

TAG-915M08 Tag is a high performance radio frequency identification (RFID) tag designed specially for mount on metal or applications where environmental extremes or exposures are required. (Bedded in cement. 3 cm, with high quality reading performance)



➤ Feature

型号 (Model)	TAG-915M08
频率范围(Frequency Range)	902-928MHz
读写灵敏度 (Read and write sensitivity)	固定式读写器 (1W,6DB): 5-10 米左右; 手持机: 2-5 米左右 (Can reach more than 5-10 meters reading distance)
芯片(Chip)	Impinj M4QT
读写协议(Protocol Support)	ISO 18000-6C,
功能(Functionality)	读/写 (Read/Write)

➤ Chip

EPC	96-EPC
DDR	512 User Bits

➤ Physical

物理尺寸(Tag Dimension)	80mm(L) x 20mm(W) x 3mm(H)
基片材料(Plate Material)	環氧+玻纖 (Epoxy Glass Fiber)
防护材料(Protective Material)	PSR4000 阻焊油墨 (PSR4000 Solder Resist Ink)
颜色(Color)	黑色 (Black)
重量(Weight)	20 g
安装方式(Mount Style)	3M 背胶、柳丁 (3M 、Rivet)

PRODUCT SPECIFICATION

➤ Environment

防水等级 (Waterproofing grade)	IP68
工作温度 (Operating Temperature)	- 40°C to +140°C
适用场合(Application)	广泛适用于户外金属设备管理、混凝土管理等，恶劣环境设备管理（埋入水泥里 3CM，具有优质的读取性能） Outdoor metal equipment management (Bedded in cement. 3 cm, with high quality reading performance)



FUWIT