

客 户

CUSTOMER_____

承 认 书

SPECIFICATION FOR APPROVAL

客 户 编 号

CUSTOMER PART NO: _____

品 名 编 号

DESCRIPTION NO. _____TAG-915M21_____

提 出 日 期

PRESENT DAY : _____2014-11-23_____

出 图 DRAWING			客户承认 CUSTOMER APPROVE
发 行 MADE	检 查 CHECKED	承 认 APPROVED	
Dence	Boby	Henry	
DATE: 2014.11.23			DATE:

深圳市铨顺宏科技有限公司

ShenZhen Fuwit Technology Co., Ltd.

表单编号: ST-R03-10

PRODUCT SPECIFICATION

TAG-915M21

- 专门为金属资产管理设计的一款标签。
- 具有抗跌落、识别距离远、抗金属性能优异、加密性好、耐高温等特点。
- 特别适用于资产管理

TAG-915M21 Tag is a high performance radio frequency identification (RFID) tag designed specially for mount on metal or applications where environmental extremes or exposures are required.

TAG-915M21 Tag can be applied using rivets, screws, or with a high bond strength acrylic adhesive, Making it ideally suited for a broad range of applications where mount on metal or easy material is required.



Unit: mm

➤ Feature

型号 (Model)	TAG-915M21
频率范围 (Frequency Range)	920-925MHz
芯片(Chip)	NXP Ucode 8 或 Ucode 9
芯片协议(Chip Protocol)	EPC Class-1 Gen2
读写协议 (Protocol Support)	ISO 18000-6C, EPC global C1Gen2
功能(Functionality)	读/写 (Read/Write)

➤ Chip

芯片容量 (Chip capacity)	Ucode9: EPC 96bit ; kill passwords 32bit ; TID 48bit
访问指令 (Access Password)	32 bits
杀死指令 (Kill Password)	32 bits
数据保存时间 (EEPROM Data Retention)	10 Year
可擦写次数 (EEPROM Write Endurance)	100,000 cycles
抗干扰性(Anti-interference)	强

PRODUCT SPECIFICATION

➤ Physical

物理尺寸(Tag Dimension)	35.2mm(L) x 31mm(W) x 7.5mm(H)
材料(Material)	ABS+陶瓷 (ABS+Ceramic)
颜色(Color)	白色 (white)
重量(Weight)	12 g
安装方式(Mounting)	3M 背胶

➤ Environment

防水等级 (Waterproofing grade)	IP67
工作温度 (Operating Temperature)	-30°C to +70°C
适用场合(Application)	资产管理 Asset management

FUWIT